



## **Specifications**



Description		250IP	350IP	450IP/450PSL	750IP	950IP	1850IPS
Excavator Weight Range Skid Steer Weight Range	Ton	0.6-2.0	1.2-3.0	2.5-4.5 (IP) (SSL)	4-8	8-12	11-16
Operating Weight	lbs	172	278	335	650	871	1898
Operating Pressure	bar	90-120	90-120	90-120	110-140	120-150	150-170
	psi	1280 -1707	1280 -1707	1280 -1707	1565 -1991	1707 -2134	2134 -2418
Required Flow	1/min	15-25	20-30	25-50	40-70	50-90	80-110
	gal/min	4-8	5-10.5	6.5-13	10.5-18.5	13-24	21-29
Tool Diameter	mm	40	45	53	68	75	100
	inch	1.57	1.811	2.087	2.677	2.953	3.937
Impact Energy	ft.lbs	150	214	236	1069	1549	3098
Gas Pressure (Back Head)	bar	16	16	16	16	16	16
	psi	232	232	232	232	232	232

Description		2650IPS	3050IPS	3650IP	4050IPS	4650IPS
Excavator Weight Range	Ton	16-26	25-32	28-32	32-36	40-48
Operating Weight	lbs	3300	4023	4729	6052	6713
Operating Pressure	bar	160-180	160-180	160-180	160-180	160-180
	psi	2276 -2560	2276 -2560	2276 -2560	2276 -2560	2276 -2560
Required Flow	1/min	100-150	120-180	150-210	180-240	200-260
	gal/min	27-40	32-48	40-56	48-63	51-69
Tool Diameter	mm	135	140	150	155	155
	inch	5.315	5.511	5.905	6.102	6.102
Impact Energy	ft.lbs.	5000	3098	7265	7966	8851
Gas Pressure (Back Head)	bar	16	16	16	16	16
	psi	232	232	232	232	232

Disclaimer: Specifications and features are subject to change for improvement in quality without prior notice. E & OE.



## EXIBENE CONDITIONS

- Micro, Mini, Midi and Heavy ranges
- Designed for extreme conditions
- High quality and proven durability
- Noise reduction technology
- Fully shock absorbed
- Energy recovery system



## rocx breaker

Ph. 877 617 7368

Web: rocxbreaker.com Email: sales@rocxbreaker.com 610 Salt Road, Webster NY 14580

